



REA ULTRAVAPOR

665 Tradewind Drive, Unit # 10
Ancaster, ON L9G 4V5
mail@ultravapor.com
1.888.860.4377

- **SATURNO MAXI** heavy duty professional saturated steam 36 kW generator, for industrial, food processing, collectivities cleaning, degreasing, sanitizing and disinfecting
- Stainless steel (AISI 304) body
- 4 electronically controlled boilers of 9 kW each
- 6 functions selectable from the grip handle
- Adjustable detergent mixture
- 3 phases vacuum socket, low tension on the control hand (12V) and low tension control panel (24V)
- starts in less than 4 mn, 3 hours autonomy in standard use
- 12 bar of pressure, 188°C in the boiler
- steam temperature at the nozzle: 150° C
- Steam production: 60 kg/hour





REA ULTRAVAPOR

665 Tradewind Drive, Unit # 10
Ancaster, ON L9G 4V5
mail@ultravapor.com
1.888.860.4377

Functions selectable from the grip handle

- 1) steam only
- 2) steam + detergent
- 3) steam + water
- 4) steam + detergent + vacuum
- 5) steam + vacuum
- 6) vacuum

Technical specifications

| | |
|----------------------------------|--|
| Power supply | 400 V / 54,7 A / 50 Hz (other on request) |
| Power | 36 kW |
| Steam production | 60 kg/hour , 188° C in the boiler , 12 bar of pressure |
| Temperature at the nozzle | 150°C |
| Water tank capacity | 120 lt , 3 hours autonomy in standard use |
| Water consumption | 60 lt/hours |
| Indicator for lack of water | yes |
| Detergent tank | 15 lt |
| Indicator for lack of detergent | yes |
| Adjustable quantity of detergent | yes |
| Maximum hose length | 14 mt |
| Electrical cable length | 10 mt |
| Markings and certifications | CE – PED – IPX 5 |
| Weight | 257 kg |
| Dimensions (mm) | L 1570 x W 750 x H 1075 |

OPTIONS

Kit for linked to the water feeding (continuous operation)

Kit for surface treatment (phosphating, passivation, etc.)